

xml-html.xsl

```

<?xml version="1.0"?>

<!-- Generic stylesheet for viewing XML -->
<xsl:stylesheet xmlns:xsl="http://www.w3.org/TR/WD-xsl">

  <!-- This template will always be executed, even if this stylesheet is not
        run on the document root -->
  <xsl:template>
    <DIV STYLE="font-family:Courier; font-size:10pt; margin-bottom:2em">
      <!-- Scoped templates are used so they don't interfere with the "kick-off"
            template. -->
      <xsl:apply-templates select=".">
        <xsl:template><xsl:apply-templates/></xsl:template>

        <xsl:template match="*">
          <DIV STYLE="margin-left:2em; color: #003366">
            &lt;<xsl:node-name/><xsl:apply-templates select="@*" />&gt;
            </DIV>
          </xsl:template>

          <xsl:template match="*[node()]">
            <DIV STYLE="margin-left:2em">
              <SPAN STYLE="color: #003366">&lt;<xsl:node-name/><xsl:apply-
templates select="@*" />&gt;</SPAN><xsl:node-name/><xsl:apply-templates select="node()" /></SPAN>
              <SPAN STYLE="color: #003366">&lt;<xsl:node-name/>&gt;</SPAN>
            </DIV>
          </xsl:template>

          <xsl:template match="@*">
            <SPAN STYLE="color:green"> <xsl:node-name/>=<SPAN
STYLE="color:red"><xsl:value-of /></SPAN></SPAN>
          </xsl:template>

          <xsl:template match="pi()">
            <DIV STYLE="margin-left:2em; color:maroon">&lt;?<xsl:node-
name/><xsl:apply-templates select="@*" />?&gt;</DIV>
          </xsl:template>

          <xsl:template match="cdata()">&lt;!CDATA[<xsl:value-of
/>]&gt;</xsl:template>

          <xsl:template match="textNode()"><xsl:value-of /></xsl:template>
        </xsl:apply-templates>
      </DIV>
    </xsl:template>
  </xsl:stylesheet>

```